

Baolifeng (BLF) Tools Co., LTD

www.blf-tools.com

CP series hydraulic pumps

- It is a single-hole operating pump which is designed with two stages of high and low pressure.
- Oil can be released quickly and it is also convenient even when there is no electricity
- With any working pressure, its function is same as electric type pump
- This type of product has operation methods like foot-stepping and manual drive. Oil pipe is 1.8 meters long and can be lengthened through discretionary purchasing
- The pressure can be kept at halted state and high pressure safety protection hydraulic valve is designed inside the pump
- Operation output pressure is 700kg/2.10.000psi. Two stages of high and low pressure are available besides quick coupling
- PT3/8" thread, oil must be replaced every half a year



Model: **CP-630**

Max output (kg/cm²/psi):700/10.000

Output (psi)-Low Pressure:350

Output (psi)-High Pressure:10.000

Oil capacity (cc):700

Weight (kg):11

Package&size (mm):645*185*185

Voltage (V/hZ):



Model: **CP-390**

Max output (kg/cm²/psi):600/8.000

Output (psi)-Low Pressure:

Output (psi)-High Pressure:8.000

Oil capacity (cc):400

Weight (kg):8

Package&size (mm):545*170*185

Voltage (V/hZ):



Model: **CP-700**

Max output (kg/cm²/psi):700/10.000

Output (psi)-Low Pressure:350

Output (psi)-High Pressure:10.000

Oil capacity (cc):900

Weight (kg):9.5

Package&size (mm):630*200*200

Voltage (V/hZ):



Model:**KB-70**

Max output (kg/cm²/psi):700/10.000

Output (psi)-Low Pressure:350

Output (psi)-High Pressure:10.000

Oil capacity (cc):0.5

Weight (kg):4

Package&size(mm):545*170*185

Voltage(V/hZ):

blf-tools.com