

Hydraulic Punch Driver

Features:

- The finished distributor, on-off case and plated can change the specification at any time. It can change the size of the tool simply, and will not destroy the surface at all after drilling hole.
- We can make the tools according to customer's requirement quick delivery.
- When order rectangle and square tools, please measure the correct dimension.

		
SYK-8	SYK-8A	SYK-8B
		
SYK-15		

Technical Data

Item. No.	Punching Range	Punching Force	Stroke	Weight	Package	Accessories	Remark
SYK-8 (A, B)	The Thickness below 3mm (16.5-60.8mm) The Thickness below 2mm (16.5-115.5mm)	10T	25mm	9.20kg	Steel Case	Round Punches: $\Phi 22$, $\Phi 27.5$, $\Phi 34.3$, $\Phi 43$, $\Phi 49$, $\Phi 60.8$ mm Small Rod(1), Big Rod(1), Gasket(1)	/
SYK-15	The Thickness below 3mm (16.5-60.8mm) The Thickness below 2mm (16.5-115.5mm) 110X110mm	15T	25mm	12.20kg	Steel Case	Round Punches: $\Phi 22$, $\Phi 27.5$, $\Phi 34.3$, $\Phi 43$, $\Phi 49$, $\Phi 60.8$ mm Square Punch: 32x32mm Small Rod(1), Big Rod(1), Gasket(1)	/

		
TPA-8	WK-8	TP-8C

Features:

- The TPA-8A is a portable hand hydraulic punch. for ease of operation and comfort the operator the tool head can be fully rotated through 360°. the working head and cylinder are made of aluminium alloy to make the weight much lighter and easy to carry.
- It gives clean perforation through 3.2mm thick mild steel with a $\Phi 60.8$ mm max. hole and 2mm with a $\Phi 115.5$ mm max. hole; 2.0mm thick stainless steel with a $\Phi 60.8$ mm max.

- The same machine with three different colour.

Technical Data

Item. No.	Punching Range	Punching Force	Stroke	Length	Weight	Package	Accessories	Remark
TPA-8	The Thickness below 3mm(16.5-60.8mm) for mild steel The Thickness below 2mm(16.5-115.5mm) for mild steel The Thickness below 2mm(16.5-60.8mm) for stainless steel	6T(60KN)	22mm	320mm	6.50kg	Plastic Box	Round Punches: Φ22, Φ27.5, Φ34.3, Φ43, Φ49, Φ60.8mm Small Rod(1), Big Rod(1), Gasket(1)	/

Features:

- The TP-8C is designed as working head with pumping body together, it's easy to operate and carry with light weight.
- It's made by high optimized material.

Technical Data

Item. No.	Punching Range	Punching Force	Stroke	Weight	Package	Accessories	Remark
TP-8C	The Thickness below 3mm(16.5-60.8mm) for mild steel The Thickness below 2mm(16.5-115.5mm) for mild steel The Thickness below 2mm(16.5-60.8mm) for stainless steel	80KN	22mm	6.50kg	Plastic Box	Round Punches: Φ22, Φ27.5, Φ34.3, Φ43, Φ49, Φ60.8mm Small Rod(1), Big Rod(1), Gasket(1)	/

Features:

- For ease of operation and comfort the operator the tool head can be fully rotated through 360°
- It gives clean perforation through 3mm thick mild steel with a Φ60.8mm max. hole and 2mm with a Φ115.5mm max hole; 2.0mm thick stainless steel with a Φ60.8mm max.

Technical Data

Item. No.	Punching Range	Punching Force	Stroke	Weight	Package	Accessories	Remark
WK-8	Φ30mm-Φ60mm (below 2mm sheet) Φ16mm-Φ30mm (below 3mm sheet)	6T(60KN)	25mm	3.50kg	Plastic Box	Round Punches: Φ22, Φ27.5, Φ34.3, Φ43, Φ49, Φ60.8mm Small Rod(1), Big Rod(1), Gasket(1)	/



CH-70



CH-60



SYD-35

Features:

- Punching the different kind of metal sheet up to 12mm.
- It can match Hand Pump CP-700 or Electric Pump ZCB 6-5.

Technical Data

Item. No.	Thickness of sheet	Punching Force	Depth of Throat	Height	Weight	Accessories	Remark
CH-70	Max. 12mm	35T	110mm	35mm	28.00kg	3/8" (Φ 10.5mm ²), 1/2" (Φ 13.8mm ²), 5/8" (Φ 17mm ²), 3/4" (Φ 20.5mm ²)	/
CH-60	Max. 10mm	31T	95mm	/	13.5kg	3/8" (Φ 10.5mm ²), 1/2" (Φ 13.8mm ²), 5/8" (Φ 17mm ²), 3/4" (Φ 20.5mm ²)	/
SYD-35	Max. 1.5mm	12T	100mm	/	12.50kg	Φ 16-Φ 35mm ²	Pump Included

Manual Punch Driver



CC-60

Technical Data

Item. No.	Punching Range	Weight	Pakage	Accessories	Remark
CC-60	Thickness below 2mm for soft metal sheet Φ 22-Φ 60.8mm	3.80kg	Plastic Box	Round Punches: Φ 22, Φ 27.5, Φ 34.3, Φ 43, Φ 49, Φ 60.8mm	It's hard to punch the thickness of metal more than 2mm

Round Punches & Square Punches



Round Punches



Square Punches

Features:

- Special size of dies can be made by us based on big quantity.

Technical Data

Round Punch Die	A	B	C	Squqre Punch Die	F						
	A1	Φ 16	B1		Φ 22	C1	Φ 63	F1	32x32mm	F7	151x151mm
	A2	Φ 20	B2		Φ 27.5	C2	Φ 76	F2	46.5x46.5mm		
	A3	Φ 26.2	B3		Φ 34	C3	Φ 80	F3	76.5x76.5mm		
	A4	Φ 32.5	B4		Φ 43	C4	Φ 89	F4	80.5x80.5mm		
	A5	Φ 39	B5		Φ 49	C5	Φ 100	F5	90.5x90.5mm		

	A6	Φ51	B6	Φ50	C6	Φ114		F6	113x113mm		
--	----	-----	----	-----	----	------	--	----	-----------	--	--